

Fitting notes for Wobble foot




Pack contents: Wobble-foot
Tools required for fitting:-
Digging Equipment

Before any digging is carried out it is important to ensure that there are no existing services buried beneath the desired placement points, i.e. electric, gas, water or drainage pipes. (Look for existing manhole covers as a clue.)

Check existing plans for services.

Make sure the required gaps between other structures and the wobble foot are maintained on all sides and that appropriate surface is underneath, for example, wood chip, rubber mats, grass mats or lawn.

Hold the tyre in place and use a spade to mark around the tyre, remembering it will be buried to half the depth of the tyre. Move the wobble foot aside and dig out the turf, placing it aside for later use. Excavate out half the depth of the tyre and form a flat bottom. Place the tyre in the excavated hole so that the foot sits level, and then back-fill with existing material. Now reinstate the turf at ground level. Replace existing top soil and compacting well in layers.



For the longevity of the wobble-foot apply boiled linseed oil to the wood when the weather is dry, twice to three times a year for best results.

If you require any further advice please contact us on 0113 2556342.

Fitting notes for Wobble foot




Pack contents: Wobble-foot
Tools required for fitting:-
Digging Equipment

Before any digging is carried out it is important to ensure that there are no existing services buried beneath the desired placement points, i.e. electric, gas, water or drainage pipes. (Look for existing manhole covers as a clue.)

Check existing plans for services.

Make sure the required gaps between other structures and the wobble foot are maintained on all sides and that appropriate surface is underneath, for example, wood chip, rubber mats, grass mats or lawn.

Hold the tyre in place and use a spade to mark around the tyre, remembering it will be buried to half the depth of the tyre. Move the wobble foot aside and dig out the turf, placing it aside for later use. Excavate out half the depth of the tyre and form a flat bottom. Place the tyre in the excavated hole so that the foot sits level, and then back-fill with existing material. Now reinstate the turf at ground level. Replace existing top soil and compacting well in layers.



For the longevity of the wobble foot apply boiled linseed oil, to the wood, when the weather is dry, twice to three times a year for best results.

If you require any further advice please contact us on 0113 2556342.